

Lighting Fixtures

Ellipsoidal

- Available in 10,19,26,36 and 50 degree beam spreads
- High Quality Optical System
- Glass Reflector
- Die Cast Aluminum Housing
- Insulated Rear handles
- Focusable Barrel
- Interchangeable Barrels
- 575HX605GLA or a 750HX755 Lamp
- Includes Gel Frame and Gobo Holder
- Tool Free Lamp Replacement
- Adjustable Shutters
- Rotating Barrel
- Tool Free centering of Lamp
- Available in White or Black
- Dimensions and Weight



10 Degree	24"L X 21"W X 21"H	22.0 LBS.
19-50 Degree	24"L X 10.5"W X 11"H	16.5 LBS.

10 Degree

Distance (ft)	80	90	100	110	120
Beam Diam.	12.8	14.4	16	17.6	19.2
FC	130	103	84	69	58

19 Degree

Distance (ft)	40	50	60	70	80
Beam Diam.	10.8	13.5	16.2	18.9	21.6
FC	180	115	80	59	45

26 Degree

Distance (ft)	30	40	50	60	70
Beam Diam.	9.9	13.2	16.5	19.8	23.1
FC	192	108	69	48	35

36 Degree

Distance (ft)	10	20	30	40	50
Beam Diam.	4.5	9	13.5	18	22.5
FC	815	203	90	50	32

50 Degree

Distance (ft)	10	20	30	40	50
Beam Diam.	5.7	11.4	13.5	22.8	28.5
FC	429	107	47	26	17

*Calculations based on 750W HX755 Lamp