




COLORado™ Zoom CW Tour

SPECIFICATIONS & FEATURES

CHAUVET®



DETAILED SPECIFICATIONS:

Output

Source: 37 (3 W) LEDs, 50,000 hours
Configuration: 37 (7 warm white (500 mA), 30 cool white (500 mA))
Installed Optic(s): Zoomable optics from 8~30°, includes 5° color blending filter
Beam Angle: 8°~30°
Field Angle: 12°~44°
Lux @ 5 m: 3,485 (8°) - 397 (30°) @ 5,600 K
Color Temperature Range: 5,270~5,600 K

Electrical

AC Voltage Range: 100~240 V, 50/60 Hz (auto-ranging)
Power Consumption: 120 V, 60 Hz 130W, 1.01 A (operating)
Power Consumption: 230 V, 50 Hz 120 W, 0.55 A (operating)
Power Linking: 9 units @ 120 V (max.), 17 units @ 230 V (max.)

Control

Control Channels: DMX: 1, 4, or 5
Stand Alone Color Mixing: Yes
Color Temperature Presets: No
Built-in Automated Programs: No
Customizable Programs: No
Recall Custom Programs: No

Physical

Dimensions: 7.9 x 9.8 x 13.1 in (203 x 250 x 334 mm)
Weight: 10.6 lbs (4.8 kg)
Power Connection: NEUTRIK® PowerCon™ power input and output connector
Control Connection: 3-pin and 5-pin DMX input and output connectors

Listings

Certification: CE, MET
Environment: IP20, dry location

Options

Optics: Color blending filters (1° or 10°)
Cabling : powerCON® Extension (18 in, 5/10/25 ft)

AT A GLANCE:

Color Temperature Mixing



Key Features:

- 37, 3 W cool and warm LEDs deliver huge output within the cool white color temperature range.
- 8~30 degree zoom allows for programming versatility in keeping light where its needed.
- Silent, fan-free operation allows for use in noise sensitive environments
- Direct 3 & 5-pin DMX in/out and powerCON in/out make connections a breeze.
- Flicker free performance, makes the fixture safe for use on camera
- Built-in color temperature presets provide predictable color every time.

About this light:

COLORado™ Zoom CW Tour features 37 white CREE LEDs providing a cool white spectrum. The variable zoom (8 to 30 degrees) serves to highlight specific areas or flood the stage. This silent fixture boasts a rugged aluminum housing that cools the fixture without the aid of fans. Secure Neutrik® powerCON® in-and-out, as well as direct DMX connections make hanging and hook-up a breeze. A 5-degree Color Blending Filter is included and enhances the smooth washing ability of this fixture.

www.chauvetlighting.com
www.chauvetlighting.co.uk

CHAUVET®